



Xclear Flex Inox UV-C



*Top view of the
PVC connection adapters mountable
on both sides*



*Bottom view of the
PVC connection adapters mountable
on both sides*



Electrics

Advantages

Flexible installation options thanks to compact design and multiple connection possibilities

- Includes 63 mm PVC connection fittings with adapters to 50 mm / 1½" female threads
- Comes with hose connectors: 1½" 40/32/25 mm
- Compact design: total unit length is only 85 cm
- Easy to integrate into new or existing filtration systems.

	40 W	75 W
Art. number	XE04402.1	XE04752.1
Type	40 W	75 W
EAN	8714404042802	8714404042819
Max. flow for 30 mJ/cm ²	20 m ³ /h	25 m ³ /h
Max. pressure	2,5 bar	2,5 bar
Diameter unit Ø	70 mm	70 mm
Length unit	75 cm	75 cm
Diameter in-outlet Ø	63 mm / 50 mm / 1½" 40/32/25/mm	63 mm / 50 mm / 1½" 40/32/25/mm
Housing material	304	304
Operating environment ballast temperature	1-40 °C	1-40 °C
Lifespan lamp	9.000 h	9.000 h
Timer	No	No
Flow switch	No	No

Spare parts

Available for:			40 W	75 W
A	F980078BUAM	Lamp VGE T5 40 W 4P Base F(bu) AM Packed	•	
	F980079BUAM	Lamp VGE T5 75 W 4P Base G AM Packed		•
B	QG017	Quartz Glass VSC 695 x 25 mm 40/75 W AM	•	•
C	E800912	Set (3pcs) O-ring for quartz glass	•	•
D	EP040012	Electrics for Black Tech 40 W	•	
	EP075017	Electrics for Black Tech 75 W (short)		•
E	H170009	Housing Black UV-C 40/75 W RVS 304	•	•
F	E800940	Set (2pcs) 3-way coupling black	•	•
G	E800941	Set (2pcs) O-rings 3-way connection	•	•
F	F990115	Reduction piece 1.5" female threaded x 63 mm out/ 50 mm in	•	•
J	3902046	Ring flat 1½"	•	•
T	E801128	Universal adaptor 1½" 40 x 32 x 25 mm PC Transparent	•	•
K	3901045	Nut for end cap Black	•	•
I	E801107	Mounting bracket 75 mm PP black	•	•
Z	SP0073	Quartz Glass Stabilizer Replacement Kit	•	•
N	F990196BU	Closing lid black	•	•

