

Xclear Pond UV-C



Advantages

A unique stand-up pond UV unit, specially designed for above-ground and basic in-ground ponds

- Plug-and-play design: powerful, affordable, and easy to install
- Choose between glued- or hose connection
- Makes it simple for all pond owners to enjoy safe and healthy water, maintained by our reliable UV-C technology
- Easy to integrate into new or existing filtration systems.



Open unit with glue socket or hose connection installation option



Closed unit with picklock installation option and mounted electrics on the back



	42 W
Art. number	XE09422
Type	42 W
EAN	8714404040853
Max. flow for 30 mJ/cm ²	14 m ³ /h
Max. pressure	1 bar - 14,5 psi
Diameter unit Ø	200 mm
Length unit	55 cm
Diameter in-outlet Ø	65 mm 38/32 mm
Housing material	High quality copolymer
Operating environment ballast temperature	1-40 °C
Lifespan lamp	9.000 h
Timer	No
Flow switch	No

Spare parts

A	3903114AM	Lamp VGE T5 42W Base Y AM Packed
B	QG129	Quartz Glass VSC 478 x 25 mm AM
C	E800912	Set (3pcs) O-ring for quartz glass
D	SP0080	Electrics for Xpose 42W LED 120/230V type F plug Packed
F	SP0078	2 x reduction piece 50mm + sealing rings Xpose
K	SP0079	2 x nut + sealing rings
T	SP0077	2 x hose adaptor flanged 65mm 38/32 + sealing rings Xpose

